

SZG301 series of modular led floodlight




Applications:

- industrial and mining enterprises large-scale plant, workshop, warehouse, equipment room, etc.
- high pole lights: highway overpasses, urban road junctions, port terminal freight yards, highway service areas, oil depots and oil tanks, railway freight forwarders, lamp bridges and lighthouses, etc.
- city square, enterprise square
- large parking lot
- indoor and outdoor sports venues
- driving, shore crane, gantry crane, etc.

Description of performances:

luminous efficiency for led	light efficacy for luminaire	energy efficiency rating of luminaire	energy saving rate @conventional lamp	led driver	wide voltage input
200 lm/W	155 lm/W	Class 2	35%	Trismart led driver	90-305 Vac
power efficiency	power factor	surge lightning protection	total harmonic distortion	beam angle	shell material
≥90%	≥0.95	6000 V	≤10%	30°/60°/90° /145°*70°	ADC12 die-cast aluminum

Product details:



dial for adjusting bracket



ADC12 die-cast aluminum heat dissipation module



led driver

Technical parameters:

Parameter items	50W	100W	150W	200W	250W	300W	400W	500W
Input voltage (V)	90-305Vac	90-305Vac	90-305Vac	90-305Vac	90-305Vac	90-305Vac	90-305Vac	90-305Vac
Power efficiency	≥90%	≥90%	≥90%	≥90%	≥90%	≥90%	≥90%	≥90%
Power factor	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95
Surge lightning protection (V)	6000	6000	6000	6000	6000	6000	6000	6000
Total harmonic distortion	≤10%	≤10%	≤10%	≤10%	≤10%	≤10%	≤10%	≤10%
Luminous efficiency for led (lm/W)	200	200	200	200	200	200	200	200
Light efficacy for luminaire (lm/W)	155	155	155	155	155	155	155	155
Energy efficiency rating of lamp	Class 2	Class 2	Class 2	Class 2	Class 2	Class 2	Class 2	Class 2
Energy saving rate	35%	35%	35%	35%	35%	35%	35%	35%
Luminous flux of luminaire (lm)	7750±5%	15500±5%	23250±5%	31000±5%	38750±5%	46500±5%	62000±5%	77500±5%
Correlated color temperature (K)	3000-6000	3000-6000	3000-6000	3000-6000	3000-6000	3000-6000	3000-6000	3000-6000
Color rendering index (Ra)	≥75	≥75	≥75	≥75	≥75	≥75	≥75	≥75
Beam angle (°)	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°	30°/60°/90° /145°*70°
LED lifespan (h)	≥100,000	≥100,000	≥100,000	≥100,000	≥100,000	≥100,000	≥100,000	≥100,000
Working temperature (°C)	-35°C - +50°C	-35°C - +50°C	-35°C - +50°C	-35°C - +50°C	-35°C - +50°C	-35°C - +50°C	-35°C - +50°C	-35°C - +50°C
IP protection	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66
Quantity of module	1	2	3	4	5	6	8	10
Brand of led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver
Installation mode of led driver	external	external	external	external	external	external	external	external
Dimensions (mm)	170*350*160	250*350*160	340*350*160	410*350*160	485*350*160	575*350*160	665*370*160	665*455*160
Weight (Kg)	2.8	3.8	4.8	5.8	6.8	7.8	11.5	13.5
Mounting mode	U-bracket	U-bracket	U-bracket	U-bracket	U-bracket	U-bracket	U-bracket	U-bracket
Warranty (year)	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years

- Note:** 1. According to GB 30255-2026: the luminous efficacy of Class 1 energy-efficient luminaire is 170-180 lm/W; for Class 2, it is 145-155 lm/W; and for Class 3, it is 100-110 lm/W.
2. Energy saving rate is compared with the conventional luminaire of class 3 energy efficiency rating.

