

SNF208 series of module led floodlight





Applications:

- industrial and mining enterprises large-scale plant, workshop, warehouse, equipment room, etc.
- high pole lights: highway overpasses, urban road junctions, port terminal freight yards, highway service areas, oil depots and oil tanks, railway freight forwarders, lamp bridges and lighthouses, etc.
- tunnel light, laneway lamp, passageway light
- city square, enterprise square, large parking lot
- indoor and outdoor sports venues
- driving, shore crane, gantry crane, etc.

Description of performances:

- Adopting Philips ultra brightness led chips with the luminous efficiency of 200 lm/W.
- The precise light distribution lens is made of polycarbonate material with a transmittance of over 95%, and the output efficiency for luminaire is up to 155 lm/W.
- The beam angles are 60 °, 90 °, 120 ° and 150 ° * 80 ° available.
- Adopting 90~305V wide input led driver, the power efficiency can reach over 93%, with good resistance to voltage fluctuations and harmonic performance, low heat generation, and fast heat dissipation.
- The heat dissipation body adopts high thermal conductivity extruded aluminum alloy, with a large surface area and fast radiation heat dissipation. At the same time, the principle of convective heat dissipation is applied inside the heat dissipation body and between modules allowing heat to be carried away by air convection.
- The connecting cable between modules is built into the heat dissipation inner body, which is resistant to oil pollution and aging, greatly extending its service life.
- The external reverse installation mode is adopted for led driver separated from the heat dissipation body, which can not only make led driver dissipate heat faster, but also prevent led driver from being washed directly by rainstorm, further improving led driver's waterproof performance.
- The lamp adopts dark sky design, which does not produce light pollution to the environment.

Heat dissipation profile:



Led driver:



Technical parameters:

Parameter items	50W	100W	150W	200W	250W
Input voltage (V)	90-305Vac	90-305Vac	90-305Vac	90-305Vac	90-305Vac
Power efficiency	≥90%	≥90%	≥90%	≥90%	≥90%
Power factor	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95
Surge lightning protection (V)	6000	6000	6000	6000	6000
Total harmonic distortion	≤10%	≤10%	≤10%	≤10%	≤10%
Luminous efficiency for led (lm/W)	200	200	200	200	200
Light efficacy for luminaire (lm/W)	155	155	155	155	155
Energy efficiency rating of lamp	Class 2	Class 2	Class 2	Class 2	Class 2
Energy saving rate	35%	35%	35%	35%	35%
Luminous flux of luminaire (lm)	7750±5%	15500±5%	23250±5%	31000±5%	38750±5%
Correlated color temperature (K)	3000-6000	3000-6000	3000-6000	3000-6000	3000-6000
Color rendering index (Ra)	≥75	≥75	≥75	≥75	≥75
Beam angle (°)	60°/90°/120°/150°*80°	60°/90°/120°/150°*80°	60°/90°/120°/150°*80°	60°/90°/120°/150°*80°	60°/90°/120°/150°*80°
LED lifespan (h)	≥100,000	≥100,000	≥100,000	≥100,000	≥100,000
Working temperature (°C)	-40°C - +50°C	-40°C - +50°C	-40°C - +50°C	-40°C - +50°C	-40°C - +50°C
IP protection	IP66	IP66	IP66	IP66	IP66
Quantity of modular (Pcs)	1	2	3	4	5
Brand of led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver	Trismart led driver
Installation mode of led driver	external	external	external	external	external
Dimensions (mm)	266*98*128	266*198*128	266*298*128	266*398*128	266*498*128
Weight (Kg)	2.2	3	4	5	6
Mounting mode	U-bracket	U-bracket	U-bracket	U-bracket	U-bracket
Warranty (year)	5 years	5 years	5 years	5 years	5 years

Note: 1. According to GB 30255-2026: the luminous efficacy of Class 1 energy-efficient luminaire is 170-180 lm/W; for Class 2, it is 145-155 lm/W; and for Class 3, it is 100-110 lm/W.

2. Energy saving rate is compared with the conventional luminaire of class 3 energy efficiency rating.



100W

150W

200W

250W