

SZG325 high power led stadium floodlight




Applications:

- indoor and outdoor sports venues
- football field and golf course
- high pole lights: highway overpasses, urban road junctions, port terminal freight yards, highway service areas, oil depots and oil tanks, railway freight forwarders, lamp bridges and lighthouses, etc.
- industrial and mining enterprises large-scale plant, workshop, warehouse, equipment room, etc.
- city square, enterprise square
- driving, shore crane, gantry crane, etc.


Description of performances:

brand of led chip	luminous efficiency for led	luminous efficacy of luminaire	Max. irradiation distance	led driver	wide voltage input
PHILIPS	≥210 lm/W	≥160 lm/W	1500 m	Inventronics led driver	90~305 Vac
power factor	surge lightning protection	total harmonic distortion	beam angle	shell material	IP protection
≥0.95	6000V	≤10%	10°/30°/45°/60°	ADC12 die-cast aluminum	IP66

Product details:



Philips super high brightness led chip



ADC12 die-cast aluminum housing




laser aiming and positioning



adjustable tilt




intercept cover (optional)



ventilation power box for fast heat dissipation

Light distribution curves:




Product profiles:


600W



1200W




1800W




Product dimensions:


600W



1200W



1800W



Technical parameters:

Parameter items	600W	1200W	1800W
Input voltage (V)	100-277Vac	100-277Vac	100-277Vac
Power efficiency	91%	91%	91%
Power factor	≥0.95	≥0.95	≥0.95
Surge lightning protection (V)	6000	6000	6000
Total harmonic distortion	≤10%	≤10%	≤10%
Brand of led chip	Philips	Philips	Philips
Luminous efficiency for led (lm/W)	≥210	≥210	≥210
Total luminous flux (lm)	160000±5%	240000±5%	360000±5%
Light efficiency for luminaire (lm/W)	≥160	≥160	≥160
Correlated color temperature (K)	3000-6500	3000-6500	3000-6500
Color rendering index (Ra)	75	75	75
Beam angle (°)	10°/30°/45°/60°	10°/30°/45°/60°	10°/30°/45°/60°
LED lifespan (h)	100,000	100,000	100,000
LED driver	Inventronics/Meanwell	Inventronics/Meanwell	Inventronics/Meanwell
Installation mode of led driver	external	external	external
Working temperature (°C)	-40~+55°C	-40~+55°C	-40~+55°C
IP protection	IP66	IP66	IP66
Dimensions (mm)	592*509*423	697*649*520	831*772*570
Weight (Kg)	20	27	47
Mounting mode	U-bracket	U-bracket	U-bracket
Warranty	5 years	5 years	5 years

Note: intercept cover optional







Test report of luminous efficiency of led chip:

EVERFINE 远方

Test report
EVERFINE LEDspec Test Report

2 Of 4

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate(2Deg): $x=0.3314$ $y=0.3399$ / $u'=0.2066$ $v'=0.4768$ $duv=-1.324e-004$

$T_c=5545K$ Dominant WL:Ld=536.9nm Purity=1.5%

Ratio:R=14.1% G=82.3% B=3.7% Peak WL:Lp=451.4nm HWL:19.7nm

Render Index:Ra=75.7

R1 =74.64 R2 =79.78 R3 =80.99 R4 =76.68 R5 =74.83

R6 =71.19 R7 =83.59 R8 =63.76 R9 =-11.12 R10=49.49

R11=73.52 R12=44.41 R13=75.32 R14=89.03 R15=71.15

TM30 Parameters: Rf = 72.8, Rg:94.9

Photo Parameters:

Flux = 143.7 lm Eff. : 208.44 lm/W Φ_e = 440.0 mW

Electrical parameters:

VF = 5.750 V IF = 119.9 mA P = 689.4 mW Ch1

LEVEL:**[OUT] WHITE:ANSI_5700K

Status: T=140.00ms Ip=47130 (72%) [HAAS1200_V1_USB] V2.00.288

Model:120MA
Tester:D.U.01.0151 24V
Temperature:25.3Deg
Manufactory:EVERFINE
Assessor:damin
System:WY + HAAS1200_V1_USB

Number:3
Date:2021-06-05 16-40
Humidity:65.0%
Remarks:---